

MATERIAL SAFETY DATA SHEET**SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Name : **PUMA™ 2040**
Common Chemical Name : BENZYLDIMETHYLAMINE
Supplier : ExpoMix Corporation
135 Park Avenue, Suite 100
Barrington, IL 60010-4370
USA
(847) 382-5238
Emergency Telephone : 800-424-9300 - CHEMTREC

SECTION 2 - INGREDIENTS

Substance / Preparation Chemical Name	: N,N-Benzyl dimethylamine (BDMA)	CAS	EINECS	Amount
		103-83-3	203-149-1	99%
Chemical Family	: Cycloaliphatic Amine			
Empirical Formula	: Mixture			
Intended Use	: Catalyst			

Occupational Exposure Limit(s), if available, are listed in section 8.

SECTION 3 - HEALTH HAZARDS

HMIS HEALTH 3 FLAMMABILITY 2 REACTIVITY 0

Hazards : Flammable. Toxic (ANSI Z129.1) by ingestion. Harmful if in contact with skin. Corrosive to eyes. Corrosive to skin. Severe eye irritant. Severe respiratory tract irritant. Severe skin irritant. May cause respiratory sensitization. May cause skin sensitization.

Routes of Exposure : Eye and Skin contact. Ingestion. Skin absorption.

Exposure Standards : Exposure limits not established by OSHA (ACGIH). Maintain air contaminant concentrations in the workplace at the lowest possible levels.

MATERIAL SAFETY DATA SHEET

Human Health Hazards

: Burns of the eye may cause blindness. Inhalation of vapors may cause irritation in the respiratory tract. Contact with undiluted product with the eyes and skin quickly causes severe irritation and pain and may cause burns, necrosis and permanent injury. Ingestion may cause death unless treated promptly. Inhalation of aerosols and mists may severely damage contacted tissue and produce scarring. Product is absorbed through the skin and may cause nausea, headache and general discomfort. This substance may cause respiratory sensitization and chronic lung toxicity to exposed workers. Repeated and/or prolonged exposures may cause allergic reaction/sensitization, adverse respiratory effects (such as cough, tightness of chest or shortness of breath), adverse eye effects (such as conjunctivitis or corneal damage), and adverse skin effects (such as rash, irritation or corrosion).

**Medical Conditions
Generally Aggravated by
Exposure
Carcinogens Under OSHA
ACGIH, NTP, IARC, Other**

: Asthma, chronic respiratory disease (e.g. Bronchitis, Emphysema), eye disease, skin disorders and allergies.

: This product contains no carcinogens in concentrations of 0.1 percent or greater.

SECTION 4 - FIRST AID

Effects and Symptoms

Ingestion

: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person. Do NOT apply mouth-to-mouth respiration. Seek medical advice.

Inhalation

: Move patient to fresh air. If breathing has stopped or is labored give artificial respiration. Supplemental oxygen may be indicated. Seek medical advice. Prevent aspiration of vomit. Turn victim's head to the side.

Skin Contact

: Remove contaminated clothing and shoes. Remove product and immediately flush affected area with water for at least 15 minutes. Destroy contaminated leather apparel. Cover the affected area with a sterile dressing or clean sheeting and transport victim for medical care. Do not apply greases and ointments. Control shock, if present. Laundry contaminated clothing prior to use.

MATERIAL SAFETY DATA SHEET

Eye Contact : Hold eye lids apart and immediately flush eyes with plenty of water for at least 15 minutes. Seek medical advice..

SECTION 5 – FIRE AND EXPLOSION DATA

Extinguishing Media : Ignition will give rise to a Class B fire. In case of large fire use: alcohol foam, water spray. In case of small fire use: carbon dioxide, dry chemical, dry sand or limestone.

Protection of Fire-Fighters : Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. May generate toxic or irritating combustion products. Vapor may form explosive mixtures with air. Contact of liquid with skin must be prevented. May spread on the surface of water. Sudden reaction and fire may result if product is mixed with an oxidizing agent. May generate carbon monoxide gas, nitrogen oxide gases and ammonia gas. Retain expended liquids from fire fighting for later disposal.

Fire Hazard Classification (OSHA/NFPA) : Class II

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Containment Techniques : Stop the leak, if possible. Reduce vapor spreading with water spray. Shut off and remove all ignition sources. Construct a dike to prevent spreading. Protect workers with water spray.

Personal Precautions : Evacuate all personnel upwind and downwind from the spill. Wear self-contained breathing apparatus, rubber boots and heavy rubber gloves. Evacuate the area.

Environmental Precautions : Do NOT release product to drain. Observe all Federal, State and local environmental regulations for appropriate product disposal.

MATERIAL SAFETY DATA SHEET

Methods for Cleaning up

: If recovery is not feasible, absorb product with dry soil, sand or vermiculite and place it in an appropriate waste chemical container for disposal. Flush area with water spray. Transfer to containers by suction. Place in metal containers for recovery and disposal. Ventilate area and wash spill site after material pickup is complete. Clean-up personnel must be equipped with self contained breathing apparatus and butyl rubber protective clothing. For large spills, recover spilled material with a vacuum truck.

SECTION 7 - HANDLING AND STORAGE

Handling

: Avoid contact with skin or eyes. Avoid breathing of vapors. Handle in well ventilated work space. Keep containers closed when empty. Empty containers may contain explosive vapors. Flush empty containers with water to remove residual combustible or flammable liquid and vapors. Smoking in area is prohibited. Label empty tank cars "Dangerous Empty". See "Flammable and Combustible Liquid Code" NFPA No. 30 (National Fire Protection Association, Boston, MA). Remove all equipment which may be a source of ignition from vicinity while handling. When handling this product, do not eat, drink or smoke.

Storage

: Keep product away from acids, oxidants, heat, flames and sparks. Keep in cool, dry ventilated storage and in closed containers. Ground all containers during transfer. Store in steel containers preferable located outdoors, above ground, and surrounded by dikes to contain spills and leaks. Electrical installations should be in accordance with Article 501 of the National Electrical Code for Class I Division 2 locations. Do not store in reactive metal containers. Recommended suitable container materials include plastic, stainless and carbon steels.

Other Precautions

: Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations (OSHA).

MATERIAL SAFETY DATA SHEET**SECTION 8 - PERSONAL PROTECTION AND EXPOSURE CONTROLS**

Engineering Measures	: Explosion proof and provide area with 12-30 air changes per hour.
Hygienic Measures	: Provide readily accessible eye wash stations and safety showers. Wash at the end of each work shift and before eating, smoking or using the bathroom. Promptly remove clothing that becomes contaminated. Discard contaminated leather articles. Laundry or discard contaminated clothing.
Occupational Exposure Limits	: No Data.
Personal Protective Equipment Respiratory System	: Not required under normal conditions in a well-ventilated area. Use appropriate NIOSH/MSHA-approved respirator during repair and cleaning of equipment, and during transfer or discharge of the product.
Skin and Body	: Impervious clothing. Slicker suit. Rubber boots. Full rubber suit (rain gear). Butyl or latex.
Hands	: Neoprene rubber gloves. Impermeable gloves. Cuffed butyl rubber gloves. The breakthrough time of the selected glove(s) must be greater than the intended use period.
Eyes	: Full face shield with goggles underneath.

SECTION 9 - TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State	: Liquid at processing temperature
Color	: Colorless at processing temperature
Odor	: Ammonia-like
Boiling Point	: 182 C (359.6 F)
Melting point	: -75 C (-103 F)
Specific Gravity (Water = 1)	: 0.91
Solubility in Water	: Slight (0.1 - 1%)
Flash Point (Closed Cup)	: 53.6 C (128.5 F)
Vapor Pressure	: 1.55 mmHg @ 21 C (70 F)
Viscosity	: 100 CPS @ 25 C (77 F)

MATERIAL SAFETY DATA SHEET**SECTION 10 – STABILITY AND REACTIVITY**

Stability	: Stable.
Conditions to Avoid(if unstable)	: Not Applicable.
Materials to Avoid	: Mineral acids(i.e. sulfuric, phosphoric, etc.). Organic acids(i.e. acetic, citric etc.). Oxidizing agents (i.e. perchlorates, nitrates etc.) Sodium or Calcium Hypochlorite. Product slowly corrodes cooper, aluminum, zinc and galvanized surfaces. Heat. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. A reaction accompanied by large heat release occurs when the product is mixed with acids. Heat generated may be sufficient to cause vigorous boiling creating a hazard due to splashing or spattering of hot material.
Hazardous Decomposition	: Nitrogen Oxide can react with water vapor to form nitric acid (TLV = 2ppm). Carbon Monoxide, Carbon Dioxide, and Nitrogen Oxides in a fire. Ammonia when heated. Irritating and toxic fumes at elevated temperatures. Nitric acid in a fire. The decomposition of nitrogen gases (except nitrous oxide) are highly toxic.
Hazardous Polymerization	: Will not occur.

SECTION 11 – TOXICOLOGICAL PROPERTIES

Toxicity Data

ORL-RAT LD50: 265 mg/kg

SKN-RBT LD50: 1660 mg/kg

Target Organs

Eye

Skin

Respiratory System

Irritation Effects Data

Corrosive to the eyes of a rabbit. Severe irritant to the skin of a rabbit.

Chronic/Subchronic Data

Component has caused allergic sensitization in animals.

MATERIAL SAFETY DATA SHEET**SECTION 12 – ECOLOGICAL INFORMATION**

Ecotoxicity Effects

No Data

Other Ecological Information

No Data

SECTION 13 – DISPOSAL CONSIDERATIONS

Methods of Disposal

: Comply with all federal, state and local environmental regulations. Almost all disposal methods are subject to regulation under RCRA. In particular, review RCRA Land Disposal Restrictions. Under some conditions, material contaminated with this product may be landfilled at appropriately permitted facilities. When a decision is made to discard this material as supplied, it is classified as a RCRA hazardous waste with the following characteristic(s): ignitable, hazardous waste number D001.

Please refer to the relevant EU regulations, in particular the guidelines / decisions of the Council regarding handling of wastes (e.g. 75/442/EEC, 91/689/EEC, 94/67/EC, 94/904/EC) as implemented in National regulations.

Must be disposed of by special means, e.g. suitable incineration, in accordance with local regulations.

SECTION 14 – TRANSPORT INFORMATION

DOT Non-Bulk Shipping : Benzyldimethylamine// 8 // UN2619 // PG II // (3)
// NAERG Guide No. 132

DOT Bulk Shipping : Refer to Bill of Lading

IMO Shipping Data : Refer to Bill of Lading

ICAO/IATA Shipping Data : Benzyldimethylamine// 8 // UN2619 // PG II // (3)
Shipment per 49 CFR 171.11 // NAERG Guide
No. 132

MATERIAL SAFETY DATA SHEET**SECTION 15 – REGULATORY INFORMATION**

US Federal Regulations**Toxic Substances Control Act (TSCA)**

All components are included in the EPA TSCA Chemical Substance Inventory.

Toxic Substances Control Act (TSCA) 12(b) Component(s)

None

OSHA Hazard Communication Standard (29 CFR1910.1200) hazard class(es)

Corrosive. Sensitizer. Toxic by Ingestion. Combustible.

EPA SARA Title III Section 312 (40CFR370) hazard class

Immediate Health Hazard. Delayed Health Hazard. Fire Hazard.

EPA SARA Title III Section 313 (40CFR372) toxic chemicals above “de minimis” level

None

State Regulations

Proposition 65 Substances (component(s) know to the Sate of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the “Safe Drinking Water and Toxic Enforcement Ac of 1986”)

None

New Jersey Trade Secret Registry Number(s)

None

EC Regulations**SECTION 16 – OTHER INFORMATION**

The environmental, health and safety information contained herein is given in compliance with statutory obligations and relates only to the substance/preparation described in this material safety data sheet. This data sheet and the information it contains is not intended to supersede any terms and conditions of sale and does not constitute a specification, promise, representation, or warranty, whether express or implied, except to the extent required by applicable law. The environmental, health and safety information contained herein is believed to be accurate based on our current knowledge. It remains the responsibility of the customer to provide a safe workplace and to comply with all applicable laws and regulations.

Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.