

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name : PUMA[®] 2142
Common Chemical Name : bis(2-dimethylaminoethyl)ether
Supplier : ExpoMix Corporation
1099 Brown Street, Unit 203
Wauconda, IL 60084
USA
Ph: (847) 487-0730
Fx: (847) 487-0217
Emergency Telephone : 800-424-9300 - CHEMTREC

SECTION 2 - INGREDIENTS

Chemical Name	CAS	EINECS	Amount
bis(2-dimethylaminoethyl)ether	3033-62-3	221-220-5	99%

Chemical Family : Tertiary Amine
Empirical Formula : C8 H20 N2O

Occupational Exposure Limit(s), if available, are listed in section 8.

SECTION 3 - HEALTH HAZARDS

HMIS HEALTH 3 FLAMMABILITY 2 REACTIVITY 0

Hazards : Combustible. Toxic (ANSI Z129.1 1988) by skin absorption. Harmful if swallowed. Corrosive to eyes. Corrosive to skin. Severe eye irritant. Severe skin irritant. Moderate respiratory tract irritant.

Routes of Exposure : Eye, skin, ingestion, skin absorption.
Exposure Standards : Exposure limits not established by OSHA (ACGIH). Maintain air contaminant concentrations in the workplace at the lowest possible levels.

SECTION 3 - HEALTH HAZARDS (CONT.)

Human Health Hazards

: Burns of the eye may cause blindness. Inhalation of vapors may cause irritation in the respiratory tract. Contact with undiluted product with the eyes or skin quickly causes severe irritation and pain and may cause burns, necrosis and permanent injury. Inhalation of aerosols, mists or fog may cause harm. Inhalation of aerosols and mists may severely damage contacted tissue and produce scarring. Product is absorbed through the skin and may cause malaise, discomfort, injury and death unless treated promptly. Repeated and/or prolonged exposures may result in: liver disorders (such as jaundice or liver enlargement), adverse respiratory effects (such as cough, tightness of chest or shortness of breath), adverse eye effects (such as conjunctivitis or corneal damage), and adverse skin effects (such as rash, irritation or corrosion). Risk of exposure to hazardous concentrations of vapor under normal working conditions in a well ventilated space is minimal. However, conditions such as spraying, or sudden release of hot liquid, which generate an aerosol, mists or fog should be avoided.

**Medical Conditions
Generally Aggravated by
Exposure
Carcinogens Under OSHA
ACGIH, NTP, IARC, Other**

: Asthma, chronic respiratory disease (e.g. Bronchitis, Emphysema), eye disease, skin disorders and allergies, liver disorders, stomach/intestinal disorders.
: This product contains no carcinogens in concentrations of 0.1 percent or greater.

SECTION 4 - FIRST AID

Effects and Symptoms**Ingestion**

: If swallowed call a physician immediately. Administer 3-4 glasses of milk or water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Do NOT apply mouth-to-mouth respiration.

Inhalation

: Move patient to fresh air. If breathing has stopped or is labored give assisted respiration. Supplemental oxygen may be indicated. Seek medical advice. Prevent aspiration of vomit. Turn victim's head to the side.

Skin Contact

: Remove contaminated clothing and shoes. Remove product and immediately flush affected area with water for at least 15 minutes. Destroy contaminated leather apparel. Cover the affected area with a sterile dressing or clean sheeting and transport victim for medical care. Do not apply greases and ointments. Control shock, if present. Launder contaminated clothing prior to use.

Eye Contact

: Hold eye lids apart and immediately flush eyes with plenty of water for at least 15 minutes. Seek medical advice.

SECTION 5 - FIRE AND EXPLOSION DATA

Extinguishing Media

: Ignition will give rise to a Class B fire. In case of large fire use: alcohol foam, water spray. In case of small fire use: carbon dioxide (CO₂), dry chemical, dry sand or limestone.
Water spray may be used to cool closed containers exposed to fire.

Protection of Fire-Fighters

: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Sudden reaction and fire may result if product is mixed with an oxidizing agent. May generate toxic or irritating combustion products. Vapor may form explosive mixtures with air. Contact of liquid with skin must be prevented. May generate carbon monoxide gas, nitrogen oxide gases and ammonia gas. Personnel in vicinity and downwind should be evacuated.
Retain expended liquids from fire fighting for disposal.

Upper Flammability Limit

: 5.1%

Lower Flammability Limit

: 1%

Auto ignition Temperature

: No Data

**Fire Hazard Classification
(OSHA/NFPA)**

: Class IIIA

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- Containment Techniques** : Stop the leak, if possible. Ventilate the space involved. Reduce vapor spreading with a water spray. Shut off and remove all ignition sources. Construct a dike to prevent spreading (includes molten liquids until they freeze). Protect workers with water spray.
- Personal Precautions** : Evacuate all personnel downwind from the spill. Wear self-contained breathing apparatus, rubber boots and heavy rubber gloves. Evacuate the area.
- Environmental Precautions** : Do NOT release product to drain. Observe all Federal, State and local environmental regulations for appropriate product disposal.
- Methods for Cleaning up** : If recovery is not feasible, absorb product with dry soil, sand or non-reactive absorbent and place it in an appropriate waste chemical container for disposal. Flush area with water spray. Transfer to containers by suction. Place in metal containers for recovery and disposal.
Ventilate area and wash spill site after material pickup is complete. Clean-up personnel must be equipped with self contained breathing apparatus and butyl rubber protective clothing. For large spills, recover spilled material with a vacuum truck.

SECTION 7 - HANDLING AND STORAGE

- Handling** : Avoid contact with skin or eyes. Avoid breathing of vapors. Handle product in a well ventilated work space and do not eat or drink. Keep containers closed when empty. Smoking in area is prohibited. Remove all equipment which may be a source of ignition from vicinity while handling.
- Storage** : Keep product away from acids, oxidants, heat, flames and sparks. Keep in cool, dry ventilated storage and in closed containers, preferably located outdoors, above ground, and surrounded by dikes to contain spills or leaks. Store away from ignition sources. Ground all containers during transfer. Store in steel containers. Do not store in reactive metal containers. Recommended suitable container materials include plastic, stainless and carbon steels.
- Other Precautions** : Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations (OSHA).

SECTION 8 - PERSONAL PROTECTION AND EXPOSURE CONTROLS

Engineering Measures	: Explosion proof and generate local exhaust with 12-30 air changes per hour.
Hygienic Measures	: Provide readily accessible eye wash stations and safety showers. Wash at the end of each work shift and before eating, smoking or using the bathroom. Promptly remove clothing that becomes contaminated. Discard contaminated leather articles. Launder or discard contaminated clothing.
Occupational Exposure Limits	: No Data.
Personal Protective Equipment	
Respiratory System	: Not required under normal conditions in a well-ventilated workplace. Use appropriate NIOSH/MSHA-respirator approved for organic vapors during repair and cleaning of equipment, during transfer or discharge of the product and during emergencies.
Skin and Body	: Impervious clothing. Slicker suit. Rubber boots. Full rubber suit (rain gear). Butyl or latex.
Hands	: Neoprene rubber gloves. Impermeable gloves. Cuffed butyl rubber gloves. Nitrile rubber gloves. Rubber Gloves. The breakthrough time of the selected glove(s) must be greater than the intended use period.
Eyes	: Full face shield with goggles underneath.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Guaranteed Values

bis(2-dimethylaminoethyl)ether	: 99% min.
Water	: 0.25% max.

Typical Values

Physical State	: Liquid
Color	: Amber to colorless
Odor	: Ammoniacal
pH	: Alkaline
Boiling Point	: 189 °C (372 °F)
Specific Gravity (Water = 1)	: 0.85
Solubility in Water	: Completely (100%)
Flash Point (Closed Cup)	: 66 °C (151 °F)
Vapor Pressure	: 0.28 mmHg @ 21 °C (70 °F)
Molecular Weight	: 160

SECTION 10 - STABILITY AND REACTIVITY

Stability	: Stable
Conditions to Avoid(if instable)	: Heat.
Materials to Avoid	: Mineral acids(i.e. sulfuric, phosphoric, etc.). Organic acids (i.e. acetic, citric etc.). Oxidizing agents (i.e. per chlorates, nitrates etc.) Reactive metals (i.e. sodium, calcium, zinc, etc.).Sodium or Calcium Hypochlorite. Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Dehydrating agents. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Materials reactive with hydroxyl compounds. A reaction accompanied by large heat release occurs when the product is mixed with acids. Heat generated may be sufficient to cause vigorous boiling creating a hazard due to splashing or spattering of hot material.
Hazardous Decomposition Products	: Nitrogen Oxide can react with water vapor to form nitric acid (TLV = 2ppm). Carbon Monoxide, Carbon Dioxide, and Nitrogen Oxides in a fire. Ammonia when heated. Irritating and toxic fumes at elevated temperatures. Nitric acid in a fire. The oxides of nitrogen gases (except nitrous oxide) emitted on decomposition are highly toxic.
Hazardous Polymerization Conditions to Avoid (if polymerization may occur)	: Will not occur. : Not applicable

SECTION 11 - TOXICOLOGICAL PROPERTIES

Acute Toxicity
 Oral (Rat) LD50: 1070 mg/kg
 Skin (Rabbit) LD50: >250 mg/kg
 Inhalation (Rat) LC50 : 2.00 mg/l/hr

Other Acute Effects
 Skin (Rabbit) LD50: 213 mg/kg

Target Organs
 Eye
 Skin
 Liver or the Hepatic System
 Respiratory System
 Digestive or Gastrointestinal System

Irritation Effects Data
 Severe irritant to the skin of a rabbit.

SECTION 11 - TOXICOLOGICAL PROPERTIES (CONT.)

Chronic/Subchronic Data

Inhalation tests have shown that exposure of rats to vapor of bis (dimethylaminoethyl) ether caused mortalities after 3 or 4 days of exposure to 90 ppm and after 6 to 9 days of exposure at 47 ppm. No mortalities occurred with exposures at 22 ppm. Subchronic exposure in test animals has caused abnormalities in lung, liver and stomach. This product has been tested and shown not to cause mild sensitization in guinea pigs.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity Effects

No Data

Other Ecological Information

No Data

SECTION 13 - DISPOSAL CONSIDERATIONS

Methods of Disposal

: Comply with all federal, state and local environmental regulations. Almost all disposal methods are subject to regulation under RCRA. In particular, review RCRA Land Disposal Restrictions. Under some conditions, material contaminated with this product may be land filled at appropriately permitted facilities.

Please refer to the relevant EU regulations, in particular the guidelines / decisions of the Council regarding handling of wastes (e.g. 75/442/EEC, 91/689/EEC, 94/67/EC, 94/904/EC) as implemented in National regulations.

Must be disposed of by special means, e.g. suitable incineration, in accordance with local regulations.

SECTION 14 - TRANSPORT INFORMATION

DOT Non-Bulk Shipping Name	:	Corrosive liquids, toxic, n.o.s. bis(2-dimethylaminoethyl)ether // 8 (6.1) // UN2922 // PG III // NAERG Guide No. 154
DOT Bulk Shipping	:	Refer to Bill of Lading
IMO Shipping Data	:	Refer to Bill of Lading
ICAO/IATA Shipping Data	:	Corrosive liquids, toxic, n.o.s. bis(2-dimethylaminoethyl)ether // 8 (6.1) // UN2922 // PG III // Shipment per 49 CFR 171.11 // NAERG Guide No. 154

SECTION 15 - REGULATORY INFORMATION

US Federal Regulations**Toxic Substances Control Act (TSCA)**

All components are included in the EPA TSCA Chemical Substance Inventory.

Toxic Substances Control Act (TSCA) 12(b) Component(s)

None

OSHA Hazard Communication Standard (29 CFR1910.1200) hazard class(es)

Corrosive. Toxic by skin absorption. Combustible

EPA SARA Title III Section 312 (40CFR370) hazard class

Immediate Health Hazard. Fire Hazard.

EPA SARA Title III Section 313 (40CFR372) toxic chemicals above "de minimis" level

None

State Regulations

Proposition 65 Substances (component(s) known to the State of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and Toxic Enforcement Act of 1986")

None

New Jersey Trade Secret Registry Number(s)

None

International Regulations:**Canada****DSL**

Included on Inventory

WHMIS Hazard Classification

Class B Division 3, Class D Division 1B, Class E Corrosive

WHMIS Ingredient Disclosure List

None

WHMIS Trade Secret Registry Number(s)

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

None

WHMIS Symbols

Test tube/hand, skull and crossbones, flames

SECTION 15 - REGULATORY INFORMATION (CONT.)

European Economic Community (EEC)**EINECS/ELINCS Master Inventory**

Included on EINECS inventory or polymer substance, monomers included on EINECS inventory or no longer polymer.

EEC Symbol

Toxic (T)

EEC Risk (R) Phrases

Causes burns (R34). Harmful if swallowed (R22). Toxic by inhalations and in contact with skin (R23/24).

EEC Safety Phrases

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S26)

Wear suitable protective clothing, gloves and eye/face protection (S36/37/39). In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).

Australia**AICS**

Included on Inventory

Japan**MITI**

Included on Inventory

Philippines**PICCS**

Included on Inventory

China**SEPA**

Included on Inventory

SECTION 16 - OTHER INFORMATION

The environmental, health and safety information contained herein is given in compliance with statutory obligations and relates only to the substance/preparation described in this material safety data sheet. This data sheet and the information it contains are not intended to supersede any terms and conditions of sale and does not constitute a specification, promise, representation, or warranty, whether express or implied, except to the extent required by applicable law. The environmental, health and safety information contained herein is believed to be accurate based on our current knowledge. It remains the responsibility of the customer to provide a safe workplace and to comply with all applicable laws and regulations. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.